



NON-FIRE RATED DOOR SYSTEMS

Vertical Coiling Insulated Service Doors

CLIMATEGUARD™ IS3000 Series



ClimateGuard IS3000 Series insulated service doors are designed for both interior and exterior use where protection against the transfer of temperature is critical for energy conservation and protection against the elements. They require a minimum amount of head room and side room and are available in a variety of finishes. Where necessary these doors can be designed as self-opening assemblies to allow egress.



ClimateGuard IS3000 Series doors are ideal for heavy traffic and high cycle applications and can be designed to sustain extreme wind loads. When climate control is necessary, ClimateGuard guarantees the highest thermal protection in the industry.



Service Doors

McKeon Door Company offers a wide selection of non-fire rated custom service doors. These assemblies can be manufactured in literally any size or for any function including insulated and sound rated, with either flat solid or perforated slats. All of these slat configurations are available in 16, 18, 20 or 22 gauge. Finishes include McKeon sterling gray, custom powder coat, stainless steel, anodized or powder-coat aluminum, galvanized or baked enamel coated steel. Service doors can be oriented to any custom-fit scenario – vertical coiling, side acting, side coiling or horizontal coiling.

MODEL	OPEN/CLOSE	FUNCTION
PF1000	Power Operator	Vertical coiling, perforated, self-opening security door
PF3000	Power or Manual* Operator	Vertical coiling perforated security door
SD3000	Power or Manual* Operator	Vertical coiling service door – high cycle, heavy use
CS3000	Power or Manual* Operator	Vertical coiling service counter shutter
IS3000	Power or Manual* Operator	Vertical coiling service door – high cycle, heavy use, insulated for sound & temperature abatement ; self-opening available
HS100	Power Operator	Horizontal coiling service door
HSL150 (Curved)	Power Operator	Horizontal and vertical coiling service door with curve

*Manual operation is limited by size, consult factory.